

NORTH SPECIAL EQUIPMENT

CATALOGUE
TECNICAL EQUIPMENT
FOR HOSPITAL
AND COMMUNITY HOUSES

Special items produced under
technical specifications
of the client



Veestraat 10,
5595GG Leende (NL)
KVK: 97099023

Phone: +31 (0) 40-2062433

E-mail: info@northspecialequipment.nl

NORTH SPECIAL EQUIPMENT

Date: Jan 17th, 2025

NO.	Product Name	Specifications	PRODUCT PICTURES	QUANTITY (SET)	UNIT PRICE EXM./USD	Total PRICE EXM./USD
1	Washing and drying machine	<ul style="list-style-type: none"> ●Washing capacity:50kg ●Drum size: 1070*610mm ●Drum volume: 523L ●Converter power: 7.5KW ●Washing speed:30-650RPM ●Size: 1600*1630*1950mm ●The washing drum is double-processed by manual grinding and electrolytic polishing, with a smooth surface and no snagging ●The entire washing cylinder system is suspended on springs and vibration reduction devices, with a vibration reduction of more than 95%, and no foundation is required for use ●It is equipped with an automatic detergent dispersing container, which will not cause soap powder accumulation, and additives cannot be fully dissolved and cause burns to the washed items. ●It uses full computer control, variable frequency speed regulation, human-computer dialogue for washing programs, and the LCD screen display is clear at a glance. It has a fault and function self-check system to make it easier to repair. 				
2	Industrial dryer	<ul style="list-style-type: none"> ●Capacity: 50kg ●Heating method:Electric ●Drum size: 1150*970mm ●Overall Size: 1240*1600*2200mm ●Computer control, fully automatic control of temperature and operation time, safer and smarter. ●The transmission system adopts two-stage V-belt transmission, with simple structure and simple maintenance. ●The fan adopts large-pitch impeller blades, and the fluff will not be blocked ●The supplementary cold air device blows cold air into the rotating cage when the drying is about to end, so that the temperature in the rotating cage is reduced in a short time and the cooling time is shortened ●The ultra-large diameter loading door is adopted, which is convenient for taking clothes. 				

3	<p>Industrial flat ironing machine</p> <ul style="list-style-type: none"> ●Roll diameter: 800mm ●Maximum ironing width: 1800mm ●Ironing speed : 1-10m/min ●Size: W2920mm* D1300mm* H1420mm ●Driven by variable frequency motor, sprocket transmission, different speeds can be adjusted at will. ●Roller φ800, width 800mm-3300mm optional. ●Different heating methods such as steam, electricity, and gas can be selected. ●Woven fabric guide belt, seamless docking, avoid pulling various linens ●A variety of roller combinations can be used to increase speed and efficiency. ●The roller is made of SUS304 stainless steel, which is corrosion-resistant for more than 10 years. 				
4	<p>Automatic clamping press</p> <ul style="list-style-type: none"> ●Overall Size: 1200*1280*1600mm ●Steam pressure:0.4-0.6MPA ●Steam consumption: 100L/min ●Platen size: 1100*360mm ●Compressed air pressure: 0.4-0.6MPA ●Compressed air consumption:18kg/h ●The frame is molded with a mold, steam heated, and equipped with a dehumidifier inside ●The material is made of high-temperature cloth and high-temperature sponge, which has good air permeability, strong water absorption, and sufficient elasticity to achieve better ironing quality ●The manual/automatic operation is simple, and the pneumatic control has a low failure rate 				
5	<p>Automatic water steam generator</p> <ul style="list-style-type: none"> ●Electric heating power 9KW ●Working voltage 380V ●Working pressure 0.45Mpa ●Water capacity 27L ●Evaporation capacity 12KG/H ●Automatic alarm and power off after water shortage to ensure that the boiler will not dry burn ●Triple safety devices of pressure switch, safety valve and safety plug, safe and reliable ●It is used with a set of automatic clamping and ironing machine 				



Vestraat 10,
5595GG Leende (NL)
KVK: 97099023
© Copyright 2025
Phone: +31 (0) 40-2062433
E-mail: info@northspecialequipment.nl